Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application. Please amend claims 35 and 40 as follows:

Listing of Claims:

RECEIVED

JAN 2 9 2004

1-34. (Cancelled)

TECHNOLOGY CENTER R3700

35. (Currently Amended) A polishing pad cartridge for installation on a planarizing machine having a supply spindle and a take-up spindle spaced apart from the supply spindle by a first distance, the cartridge comprising:

a cartridge frame <u>comprising a linear member</u> having a first attachment portion and a second attachment portion spaced apart from the first attachment portion by a second distance, the second distance being approximately equal to the first distance between the supply spindle and the take-up spindle;

a supply roll rotatably coupled to the frame at the first attachment portion;

a take-up roll rotatably coupled to the frame at the second attachment portion; and

an elongated polishing pad having a first end attached to the supply roll and a second end attached to the take-up roll.

- 36. (Original) The cartridge of claim 35 wherein the elongated polishing pad is a fixed abrasive polishing pad that includes a suspension medium and a plurality of abrasive elements fixedly distributed in the suspension medium.
- 37. (Original) The cartridge of claim 36 wherein the supply spindle and the take-up spindle each have projections extending away therefrom and the supply roll and the take-up roll each include apertures configured to receive the projections.
- 38. (Original) The cartridge of claim 35 wherein the polishing pad includes polyurethane.



- 39. (Original) The cartridge of claim 35 wherein the supply roll includes an axle having a portion extending beyond an edge of the polishing pad and the first attachment portion of the frame includes an opening sized to rotatably receive the portion of the axle.
- 40. (Currently Amended) A polishing pad cartridge for installation on a planarizing machine having a supply spindle and a take-up spindle spaced apart from the supply spindle by a first distance, the cartridge comprising:

a supply roll having a first aperture for receiving the supply roll spindle; a take-up roll having a second aperture for receiving the take-up roll spindle; and an elongated member coupling the supply roll and the take-up roll; and

an elongated polishing pad having a first end attached to the supply roll and a second end attached to the take-up roll, the elongated polishing pad being at least partially coiled on the supply roll, the take-up roll being movable relative to the supply roll to separate the first and second apertures by a second distance approximately equal to the first distance while the polishing pad is attached to the supply roll and the take-up roll.

- 41. (Original) The cartridge of claim 40 wherein the elongated polishing pad is a fixed abrasive polishing pad that includes a suspension medium and a plurality of abrasive elements fixedly distributed in the suspension medium.
- 42. (Original) The cartridge of claim 40 wherein the supply spindle and the take-up each have projections extending away therefrom and the supply roll and the take-up roll each include apertures configured to receive the projections.
- 43. (Original) The cartridge of claim 40 wherein the polishing pad includes polyurethane.

44-76. (Cancelled)

